



- 8 FOR REFERENCE PURPOSE ONLY, THESE SURFACES TO ALIGN WHEN SLIDE IS IN CLOSED POSITION
- USE NUMBER 8, 100° FLAT HEAD MACHINE SCREWS FOR MOUNTING THROUGH THE SLIDE CHANNELS.
 - CABINET SECTION OR CHASSIS SECTION MAY BE PURCHASED SEPARATELY AND ARE INTERCHANGEABLE.
 - THE SLIDE SHOWN CAN BE USED AS A LEFT-HAND OR RIGHT-HAND SLIDE. WHEN USED AS A RIGHT-HAND SLIDE, THE REAR LOCK WILL BE ON THE TOP SIDE OF THE SLIDE.
 - THIS IS A FRICTION SLIDE
 - THE SLIDE LOCKS IN THE OPEN POSITION AND IS PROVIDED WITH A QUICK DISCONNECT OF THE CHASSIS SECTION.
 - FINISH: ALL SLIDE CHANNELS ARE ANODIZED PER MIL-A-8625, TYPE II, CLASS 2, DYED BLACK. THE INTERMEDIATE SLIDE CHANNEL IS DRY FILM LUBRICATED PER MIL-PRF-46010 T1. CRES COMPONENTS ARE PASSIVATED PER SAE-AMS-2700.
 - MATERIAL: SLIDE CHANNELS ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS WITH A TENSILE STRENGTH OF 35,000 PSI MINIMUM (PER ASTM B221). COMPONENT PARTS ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS AND CORROSION RESISTANT STEEL.

PART NO.	SLIDE LENGTH	SLIDE TRAVEL	CHASSIS SECTION				CABINET SECTION				LOAD RATING (PER PAIR)	
			A	B	C	D	E	F	G	H		J
525QD-10	10.00	10.00	2.750	-	-	7.625	-	-	-	5.250	8.250	170 lbs.
525QD-12	12.00	12.00	3.750	-	-	9.500	-	-	-	7.250	10.250	181 lbs.
525QD-14	14.00	14.00	4.000	-	9.750	11.250	-	-	6.250	9.250	12.250	174 lbs.
525QD-16	16.00	16.00	4.500	-	11.000	13.250	-	-	8.250	11.250	14.250	162 lbs.
525QD-18	18.00	18.00	5.500	-	12.000	15.250	-	-	10.250	13.250	16.250	154 lbs.
525QD-20	20.00	20.00	4.000	7.000	14.000	17.250	-	9.250	12.250	15.250	18.250	147 lbs.
525QD-22	22.00	22.00	4.000	8.000	15.000	19.250	-	11.250	14.250	17.250	20.250	140 lbs.
525QD-24	24.00	24.00	5.000	9.000	16.500	21.250	-	13.250	16.250	19.250	22.250	134 lbs.
525QD-26	26.00	26.00	5.500	9.500	17.500	23.250	12.250	15.250	18.250	21.250	24.250	130 lbs.
525QD-28	28.00	28.00	5.500	10.000	18.750	25.250	14.250	17.250	20.250	23.250	26.250	128 lbs.
525QD-30	30.00	30.00	6.000	12.000	20.000	27.250	16.250	19.250	22.250	25.250	28.250	116 lbs.

JONATHAN
Engineered Solutions

Irvine Technology Center
410 Exchange, Suite 200
Irvine, CA 92602
Tel. (714) 665-4400
Fax: (714) 368-7002
Website: www.jonathanengr.com
Engineer - Production - Integration/ Subassembly - Logistics
United States - Mexico - China - Taiwan

TOLERANCES UNLESS OTHERWISE NOTED				PART NUMBER: 525QD		DESCRIPTION: ALUMINUM SERIES 525QD	
.XX	.XXX	ANGLES	HOLES	DATE: 06/02/15			
± .01	± .005	± 1°	± .005				
SHEET 1 OF 1				COPYRIGHT © 2012 JONATHAN ENGINEERED SOLUTIONS			