


END VIEW

PART NO.	A	B	C	D	E	F	G	H	J	K	M	LOAD RATING
9000-12	12.00	12.06	2.00	6	10	-	-	-	-	4.000	8.000	400 lbs
9000-14	14.00	14.06	4.00	6	10	4.000	-	-	-	-	8.000	335 lbs
9000-16	16.00	16.06	2.00	8	12	4.000	-	-	-	8.000	12.000	285 lbs
9000-18	18.00	18.06	4.00	8	12	4.000	-	-	-	8.000	12.000	250 lbs
9000-20	20.00	20.06	2.00	10	14	4.000	-	-	8.000	12.000	16.000	220 lbs
9000-22	22.00	22.06	4.00	10	14	4.000	-	-	8.000	12.000	16.000	200 lbs
9000-24	24.00	24.06	2.00	12	16	4.000	-	8.000	12.000	16.000	20.000	180 lbs
9000-26	26.00	26.06	4.00	12	16	4.000	-	8.000	12.000	16.000	20.000	165 lbs
9000-28	28.00	28.06	2.00	14	18	4.000	8.000	12.000	16.000	20.000	24.000	155 lbs

- 6. HOLES OTHER THAN SHOWN MAY BE IN THE SLIDE MEMBERS AT JONATHAN OPTION.
- 5. THIS SLIDE MUST BE DISCONNECTED TO MOUNT CHASSIS SECTION.
- 4. REMOVAL OF CHASSIS SECTION FROM SLIDE IS OBTAINED BY REMOVING A SOCKET HEAD CAP SCREW ON THE RIGHT SIDE NEAR THE REAR OF THE CHASSIS SECTION. (USE .31 HEX TOOL)
- 3. SLIDE DOES NOT LOCK IN OPEN OR CLOSED POSITION.
- 2. FINISH: COMMERCIAL CLEAR ZINC PLATING
- 1. MATERIAL: SLIDE MEMBERS ARE MADE FROM 12 GAGE (.105) STEEL.



Jonathan
Engineered Solutions

Irvine Technology Center
410 Exchange, Suite 200
Irvine, CA 92602
Tel: (714) 665-4400
Fax: (714) 368-7002
Website: www.jonathanengr.com
Engineer - Production - Integration/ Subassembly - Logistics
United States - Mexico - China - Taiwan

<i>TOLERANCES UNLESS OTHERWISE NOTED</i>				PART NUMBER :		DESCRIPTION :	
				9000		STEEL	
				DATE :		SERIES 9000	
				10/10/11		LOAD RATING : 155-400 LBS	
.XX .XXX ANGLES HOLES ± .03 ± .010 ± 2° ± .005							
SHEET 1 OF 1				COPYRIGHT © 2009 JONATHAN ENGINEERED SOLUTIONS			