



- 7 SLIDE LOCKS IN THE CLOSED POSITION
PUSH LEVER TO RELEASE SLIDE FROM LOCKED POSITION.
- 6 THESE SURFACES ALIGN WHEN SLIDE IS IN CLOSED POSITION.
- 5. SLIDE FEATURES QUICK DISCONNECT OF CHASSIS SECTION.
- 4. LEFT HAND SLIDE AS SHOWN, RIGHT HAND SLIDE OPPOSITE.
- 3. USE #8 X 100° FLAT HEAD MACHINE SCREWS FOR MOUNTING THRU SLIDE MEMBERS.
- 2. FINISH: CHANNELS ARE ANODIZED PER MIL-A-8625, TYPE II, CLASS I.
CRES PARTS PASSIVATED PER SAE-AMS-2700.
- 1. MATERIAL: CHANNELS ARE FABRICATED FROM HIGH STRENGTH ALUMINUM ALLOYS WITH TENSILE STRENGTH OF 35,000 PSI MIN.
(PER ASTM B221). COMPONENT PARTS ARE STAINLESS STEEL AND HIGH STRENGTH ALUMINUM. BALL BEARINGS ARE 440 CRES.

SERIES LENGTH	SLIDE LENGTH	SLIDE TRAVEL	MOUNTING HOLE PATTERN														LOAD RATING	SLIDE WEIGHT
			CABINET SECTION							CHASSIS SECTION								
PART NO.	L	T	A	B	C	D	E	F	G	H	J	K	M	N	R	S	PER PAIR	
129TLC-6	6.00	6.00	-	-	2.000	-	-	-	4.250	-	-	-	-	-	-	3.500	98 LBS	.269 LBS
129TLC-7	7.00	7.00	-	-	3.000	-	-	-	5.250	2.500	-	-	-	-	-	4.500	98 LBS	.307 LBS
129TLC-8	8.00	8.00	3.000	-	4.000	-	-	-	6.250	2.750	-	-	-	-	-	5.500	101 LBS	.346 LBS
129TLC-9	9.00	9.00	3.000	-	5.000	-	-	-	7.250	3.250	-	-	-	-	-	6.500	101 LBS	.384 LBS
129TLC-10	10.00	10.00	4.000	-	6.000	-	-	-	8.250	3.250	-	-	-	-	-	6.500	108 LBS	.422 LBS
129TLC-11	11.00	11.00	4.000	-	7.000	-	-	-	9.250	2.500	-	-	6.000	-	-	8.500	108 LBS	.460 LBS
129TLC-12	12.00	12.00	4.000	-	8.000	-	-	-	10.250	2.500	-	-	6.000	-	-	8.500	104 LBS	.498 LBS
129TLC-13	13.00	13.00	5.500	-	9.000	-	-	-	11.250	2.500	-	-	6.000	-	-	8.500	104 LBS	.537 LBS
129TLC-14	14.00	14.00	5.500	-	10.000	-	-	-	12.250	2.500	-	5.000	9.000	-	-	11.500	101 LBS	.575 LBS
129TLC-15	15.00	15.00	5.500	-	11.000	-	-	-	13.250	2.500	-	5.000	9.000	-	-	11.500	101 LBS	.613 LBS
129TLC-16	16.00	16.00	5.500	-	7.500	9.750	12.000	-	14.250	2.500	-	5.000	9.000	-	-	11.500	98 LBS	.651 LBS
128TLC-17	17.00	17.00	5.500	-	8.500	10.750	13.000	-	15.250	2.500	-	5.000	9.000	-	-	11.500	98 LBS	.689 LBS
129TLC-18	18.00	18.00	5.500	-	9.500	11.750	14.000	-	16.250	2.500	-	5.000	8.500	11.000	-	13.500	94 LBS	.727 LBS
129TLC-19	19.00	19.00	5.500	-	10.500	12.750	15.000	-	17.250	2.500	-	5.000	8.500	11.000	-	13.500	94 LBS	.766 LBS
129TLC-20	20.00	20.00	5.500	-	11.500	13.750	16.000	-	18.250	2.500	-	5.000	8.500	11.000	-	13.500	90 LBS	.804 LBS
129TLC-21	21.00	21.00	5.500	-	12.500	14.750	17.000	-	19.250	2.500	5.000	7.500	11.500	14.000	-	16.500	90 LBS	.842 LBS
129TLC-22	22.00	22.00	5.500	-	13.500	15.750	18.000	-	20.250	2.500	5.000	7.500	11.500	14.000	-	16.500	87 LBS	.880 LBS
129TLC-23	23.00	23.00	5.500	-	12.250	14.500	16.750	19.000	21.250	2.500	5.000	7.500	11.000	13.500	16.000	18.500	87 LBS	.918 LBS
129TLC-24	24.00	24.00	5.500	-	13.250	15.500	17.750	20.000	22.250	2.500	5.000	7.500	11.000	13.500	16.000	18.500	85 LBS	.957 LBS
129TLC-25	25.00	25.00	5.500	11.250	14.250	16.500	18.750	21.000	23.250	2.500	5.000	7.500	13.000	15.500	18.000	20.500	85 LBS	.995 LBS
129TLC-26	26.00	26.00	5.500	11.250	15.250	17.500	19.750	22.000	24.250	2.500	5.000	7.500	13.000	15.500	18.000	20.500	80 LBS	1.033 LBS

JONATHAN[®]
Engineered Solutions

Irvine Technology Center
410 Exchange, Suite 200
Irvine, CA 92602
Tel. (714) 665-4400
Fax: (714) 368-7002
Website: www.jonathanengr.com
Engineer - Production - Integration/ Subassembly - Logistics
United States - Mexico - China - Taiwan

TOLERANCES UNLESS OTHERWISE NOTED				PART NUMBER : 129TLC		DESCRIPTION : ALUMINUM SLIDE SERIES 129TLC	
.XX	.XXX	ANGLES	HOLES	DATE : 03/24/16			
± .01	± .005	± 1°	± .005				
SHEET 1 OF 1				COPYRIGHT © 2012 JONATHAN ENGINEERED SOLUTIONS			